

AR CLEANING KIT

USER MANUAL



FF38000



Engineered for high intensity, fast-paced situations, from paintball games to tactical training simulations to home defense, Firefield products are designed for the next generation shooter and serious gun enthusiast. Our goal is to provide optimal solutions for demanding tactical, hunting and competitive training situations.

Firefield products are tested for durability in extreme terrain and extreme climates. Consisting of shooting accessories compatible with extreme shooting guns, AR-I5s, tactical carbines, air guns, shotguns and pistols, the Firefield product line includes: riflescopes, red dot sights, reflex sights, laser sights, magnifiers, bore sights, night vision, digital night vision, flashlights, spotting scopes, rails and mounts.

Delivering high quality and exceptional durability to every intense moment, Firefield is the key to victory. Transform fear to power, panic to excitement and chaos to glory with Firefield units.

To view this manual in other languages, or for more information please visit www.fire-field.com.

© Sellmark Corporation, all rights reserved

www.fire-field.com

AR CLEANING KIT

Designed to clean all .223 and .308 AR platform rifles, the Firefield AR Cleaning Kit has the tools you need to keep your firearm firing on all cylinders. Made to make your personal MSR look and feel like the day you bought it; the kit includes a bore brush, chamber brush and bore mop for both calibers, as well as 20 cleaning patches, brass rods, flexible cable, lubrication applicator bottle and a small brush and large brush.

FEATURES:

- Compact carrying case
- 33 inch cable for easy cleaning
- Chamber cleaning brush for complete cleaning of the chamber star
- Small and large brush for cleaning the exterior
- Included lubrication applicator so you can keep your favorite gun lube with your cleaning kit on the go

INCLUDED: OTY:

| | _ |
|---|-----|
| Bore brush 223 | - 1 |
| Bore brush 308 | - 1 |
| Chamber brush 223 | - 1 |
| Chamber brush 308 | - 1 |
| Bore Mop 223 | - 1 |
| Bore Mop 308 | - 1 |
| Slotted tip | - 1 |
| Round cleaning patches | 25 |
| Square cleaning patches | 25 |
| Handle | - 1 |
| Brass rods | - 1 |
| Flexible cable | - 1 |
| Lubrication applicator bottle | - 1 |
| Small brush | 1 |
| Large brush | - 1 |

DIAGRAM

- Bore brush 223
- Bore brush 308
- Chamber brush 223
- Chamber brush 308
- Bore Mop 223
- Bore Mop 308
- Slotted tip
- Round cleaning patches
- Square cleaning patches
- Handle
- Brass rods
- Flexible cable
- Lubrication applicator bottle
- Small brush
- Large brush



TECHNICAL SPECIFICATIONS

| TECHNICAL SPECIFICATIONS | FF24063 |
|--------------------------|------------|
| Length | 5"/127mm |
| Width | 4.2"/107mm |
| Height | 2.8"/72mm |
| Weight | 9.4 |
| Material (bag) | 600D Nylon |

USING THE CHAMBER BRUSH:

- I. Separate the upper receiver from the lower receiver and remove the bolt carrier group and charging handle.
- 2. Attach the 3 brass rods to the handle.
- 3. Attach the chamber brush of the appropriate caliber to the end of the brass brush.
- 4. Insert the chamber brush in to the chamber through the bolt carrier slot.
- 5. Push and pull it through the star chamber to clean the chamber of any debris.



USING THE BRUSHES:

- I. The brushes attach to the handle on the side opposite the threaded insert. Simply push them in to the hole in the handle.
- 2. These can be used for brushing the insides of the receiver



USING THE BORE BRUSHES, BORE MOP, AND SLOTTED TIP:

- 1. Attach the bore brush/ bore mop/ slotted tip for the appropriate caliber to the flexible cable. If using the slotted tip insert a cleaning tip through the slot
- 2. Hold upper receiver with barrel oriented in a vertical direction.
- 3. Feed the opposite end of the cable through the barrel until it comes out the other side of the barrel.
- 4. Insert the end of the flexible cable in to the hole in the side of the handle that does not have a ledge.
- 5. Slide over to opposite side of the slot so that it locks in when pulled.
- 6. Pull the cable all the way through.
- 7. Repeat steps 2-6 until bore is cleaned





USING THE LUBRICATION APPLICATOR

- 1. The bottle can be filled with your lubrication of choice by removing the cap and pulling off the applicator tip.
- 2. Apply lubrication where needed



| Notes | |
|-------|--|
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |

FIREFIELD WARRANTY

Please visit www.fire-field.com for warranty details and information.

www.fire-field.com